

## 6 outlet 2 pack Surge Protector with 3' CORD GXS-701KR

You can stop destructive surges from crippling you hardware and scrambling software data with a GoldX® surge protector. This product is designed to detect and dissipate damaging power surges before they harm your electronic equipment.



### Features:

- 6 grounded power outlets
- 15 amp circuit breaker
- Home or office use
- Two pack -- buy one get one free

### Protect your Computer Systems from:

- System crashes
- Corrupted data files
- Power disturbances
- Disk drive errors
- Hardware damage

### SPECIFICATIONS

UL clamping Voltage	400V (Hot to Neutral)
Maximum Energy Displacement	90 Joules
Maximum Current	4500 A
Maximum Spike Voltage	6000V
Response Time	<1 Nanosecond

### \$1,500 Connected Equipment Warranty:

If, during the time period listed for you model, any equipment properly connected to the Surge Protector is damaged by a transient spike or surge (as defined by industry standards) that enters the equipment through a properly installed GoldX® Surge Protector, Jo-Dan International (JDI) will reimburse your reasonable cost to repair or replace the damaged equipment (at the option of JDI) up to the maximum U.S. dollar amount listed for your specific surge protector. Please see the installation guide for your model for additional details.

## 6-OUTLET SURGE PROTECTOR GXS-702R

You can stop destructive surges from crippling your hardware and scrambling software data with a GoldX® surge protector. This product is designed to detect and dissipate damaging power surges before they harm your electronic equipment.



### Features:

- 6 grounded power outlets
- Surge protection LED indicator
- EMI/RFI noise filtering
- Illuminated on/off switch
- Mounting bracket

### Protect your Computer Systems from:

- System crashes
- Corrupted data files
- Power disturbances
- Disk drive errors
- Hardware damage

### TECHNICAL SPECIFICATIONS

#### ELECTRICAL RATING:

125 V, 15 A, 60 Hz, 1875 Watts

#### SURGE PROTECTION PERFORMANCE:

UL Clamping Voltage	400V (Hot-Neutral, Hot-Ground, Neutral-Ground)
Maximum Energy Displacement	270 Joules
Maximum Current	13500 A
Maximum Spike Voltage	6000 V
Response Time	< 1 Nanosecond

#### EMI/RFI NOISE FILTER

Frequency Range	100 KHz - 50 MHz
Attenuation	4 to 52 dB

### \$ 10,000 Connected Equipment Warranty:

If, during the time period listed for your model, any equipment properly connected to the Surge Protector is damaged by a transient spike or surge (as defined by industry standards) that enters the equipment through a properly installed GoldX® Surge Protector, Jo-Dan International (JDI) will reimburse your reasonable cost to repair or replace the damaged equipment (at the option of JDI) up to the maximum U.S. dollar amount listed for your specific surge protector. Please see the installation guide for your model for additional details.

## 6-OUTLET SURGE PROTECTOR GXS-703KM

This GoldX® Products surge protector allows connection for up to 6 devices with DSL and fax/modem protection included. Sliding outlet cover for child protection. 6' power cord. Connected equipment warranty of \$10,000.



### Features:

- 24 Karat Lifetime Warranty
- Fax/Modem Line Protection
- Sliding Outlet Cover for Child Protection
- 6 Grounded Power Outlets
- Surge Protection LED Indicator
- EMI/RFI Noise Filter
- Illuminated On/Off Switch
- Mounting Bracket
- **Free** 1 Outlet Surge Protector

### TECHNICAL SPECIFICATIONS

#### ELECTRICAL RATING:

125 V, 15 A, 60 Hz, 1875 Watts

#### SURGE PROTECTION PERFORMANCE:

UL Clamping Voltage	400V (Hot-Neutral, Hot-Ground, Neutral-Ground)
Maximum Energy Displacement	270 Joules
Maximum Current	13500 A
Maximum Spike Voltage	6000 V
Response Time	< 1 Nanosecond

#### EMI/RFI NOISE FILTER:

Frequency Range	100 KHz - 50 MHz
Attenuation	4 to 52 dB

#### FAX/MODEM PROTECTION PERFORMANCE:

UL Clamping Voltage	400 V
Maximum Energy Displacement	70 Joules

#### TECHNICAL SPECIFICATIONS – 1 OUTLET SURGE

UL Clamping Voltage	330V
Maximum Energy	270 Joules
Maximum Current	13500 A
Maximum Spike Voltage	6000V
Response Time	<1 Nanosecond

#### EMI/RFI NOISE FILTER

Frequency Range	100KHz-50MHz
Attenuation	4 to 52 dB

### \$10,000 Connected Equipment Warranty:

If, during the time period listed for you model, any equipment properly connected to the Surge Protector is damaged by a transient spike or surge (as defined by industry standards) that enters the equipment through a properly installed GoldX® Surge Protector, Jo-Dan International (JDI) will reimburse your reasonable cost to repair or replace the damaged equipment (at the option of JDI) up to the maximum U.S. dollar amount listed for your specific surge protector. Please see the installation guide for your model for additional details.

© Copyright 2007 Jo-Dan International, Inc. all rights reserved. Plus Series®, PowerCore®, QuickConnect®, Share Plus®, and GoldX® Products are registered trademarks of Jo-Dan International, Inc. All other trademarks and registered trademarks are the property of their respective owners. Designed in USA. Made in China. One or more of the following patents may apply: D494,935, D494,934, D494,932, D493,453, 6,755,676, D490,702, 6,736,658, 6,726,509, 6,716,047, D485,752, D484,044, D481,629, D481,628, 6,607,408, D478,001, D478,000, D468,635, 6,479,607, D465,223,6,454,584, D462,612, D452,427, D452,426, D451,888, D451,480, D450,303, D448,736, D444,772, D443,862, D443,593, D442,919, D442,556, D442,555, 5,788,521, 5,658,158, 5,334,033, 5,292,257. D503,882; 6,843,684; 6,854,989; 6,872,086; D506,386; 6,905,374; D509,797; 6,991,483; D513,976; 7,004,787; 7,028,114; D519,925; D522,507; 7,258,572. Other patents pending

## 8-OUTLET SURGE PROTECTOR GXS-710M

You can stop destructive surges from crippling your hardware and scrambling software data with a GoldX® surge protector. This product is designed to detect and dissipate damaging power surges before they harm your electronic equipment.



### Features:

- Fax/modem line protection
- 8 grounded power outlets
- Surge protection LED indicator
- Ground LED indicator
- Surge protection alarm with auto current shut off
- EMI/RFI noise filtering
- Illuminated on/off switch
- Extra space for AC adapters

### Protect your Computer Systems from:

- System crashes
- Corrupted data files
- Power disturbances
- Disk drive errors
- Hardware damage

### TECHNICAL SPECIFICATIONS

#### ELECTRICAL RATING:

125 V, 15 A, 60 Hz, 1875 Watts

#### SURGE PROTECTION PERFORMANCE:

UL Clamping Voltage	330V (Hot-Neutral, Hot-Ground, Neutral-Ground)
Maximum Energy Displacement	1140 Joules
Maximum Current	27000 A
Maximum Spike Voltage	6500 V
Response Time	< 1 Nanosecond

#### EMI/RFI NOISE FILTER:

Frequency Range	100 KHz - 50 MHz
Attenuation	4 to 52 dB

#### FAX/MODEM PROTECTION PERFORMANCE:

UL Clamping Voltage	400 V
Maximum Energy Displacement	106 Joules

### **\$30,000 Connected Equipment Warranty:**

If, during the time period listed for your model, any equipment properly connected to the Surge Protector is damaged by a transient spike or surge (as defined by industry standards) that enters the equipment through a properly installed GoldX® Surge Protector, Jo-Dan International (JDI) will reimburse your reasonable cost to repair or replace the damaged equipment (at the option of JDI) up to the maximum U.S. dollar amount listed for your specific surge protector. Please see the installation guide for your model for additional details